

ASIAN VEHICLES

EXTENDED LIFE RED/PINK ANTIFREEZE + COOLANT

DESCRIPTION

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE +

COOLANT for **ASIAN VEHICLES** is a line of premium coolants specifically designed to match the technology and color requirements of **Asian** vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT

for **ASIAN VEHICLES - RED/PINK** is an ethylene glycol-based antifreeze/coolant specifically developed for use in any Asian vehicle requiring a Red or Pink phosphate-enhanced organic acid technology (POAT) formulation. It contains high-quality organic acid corrosion inhibitors and is free of borate, nitrite, silicate and amines chemicals.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE +

COOLANT for **ASIAN VEHICLES - RED/PINK** meets the performance requirements of ASTM D3306 and JIS K2234. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 150,000 miles or 5 years.

FEATURES & BENEFITS

- Matches each Asian vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and JIS K2234
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT concentrate to perform a complete flush/fill or top-off.

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY 50/50 PREDILUTED ANTIFREEZE + COOLANT when just topping off your system.

A PERFECT MATCH FOR EVERY VEHICLE



FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM			
	Freezing Down to	Boiling Up to*		
50/50	-34°F (-36°C)	265°F (129°C)		
60/40	-62°F (-52°C)	270°F (132°C)		
70/30	-84°F (-64°C)	276°F (135°C)		

*Using a 15 psig (103 kPa) pressure cap in good condition



Available in both 50/50 Prediluted and Concentrate





ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT

APPLICATIONS

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for **ASIAN VEHICLES - RED/PINK** is specifically engineered for use in all Asian vehicles requiring a RED/PINK PHOSPHATE-ENHANCED ORGANIC ACID TECHNOLOGY (POAT) extended life antifreeze/coolant:

- Lexus: 1990 and up
- Scion: 2004 and up
- Toyota: 1990 and up

PROPERTIES					
	ASTM TEST METHOD	CONCENTRATE	PREDILUTED (50/50)	ASTM D3306 Limits	
Appearance	Visual	Red	Red	Distinctive	
pH, (50% vol)	D1287	7.7	7.7	7.5-11.0	
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ / 1.065 min ²	
Boiling point ³ , °C (°F)	D1120	162.8 (325)	109.5 (229.1)	108 (226) Min	
Freezing point, °C (°F)	D1177		-37.9 (-36.2)	-36.4 (-33.5) Max	
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect	
Total water, mass %	D1123	<5	50	5 Max ¹	
Ash content, mass %	D1119	1.62	0.82	5 Max ¹ / 2.5 max ²	
Chloride, ppm	D3634	<25	<25	25 Max	

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



Part #	Unit	Pack/Size	Dimensions	Unit Wt. (Ibs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PARØB3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PARB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PARØB1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PARB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Original Equipment Technology Asian RED/PINK Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Original Equipment Technology Asian RED/PINK Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from **peakauto.com**. Always dispose of used coolant in accordance with local, state and Federal guidelines.



To order, please call Old World Industries Customer Service at 1-800-323-8755 Old World Industries, LLC. Northbrook, IL 60062 • 800-323-5440 Peakauto.com

Manufactured for Old World Industries, LLC. Northbrox, ILG 0002, 299-7234 MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT ©2020 Old World Industries, LLC. All Rights Reserved, PEAK and PEAK ORIGINAL EQUIPMENT TECHNOLOGY are trademarks of Old World World 06-10-2020