

DESCRIPTION

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for EUROPEAN VEHICLES is a line of premium coolants specifically designed to match the technology and color requirements of European vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for EUROPEAN VEHICLES - VIOLET is an ethylene glycol-based antifreeze/coolant specifically developed for use in any European vehicle requiring a Violet silicate-enhanced organic acid technology (Si-OAT) formula. It contains high-quality organic acid corrosion inhibitors and is free of borate, nitrite, nitrate, phosphate and amines chemicals.

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for EUROPEAN VEHICLES - VIOLET meets the performance requirements of ASTM D3306 and BS 6580. With a complete flush and fill, PEAK guarantees this coolant will provide service life protection of up to 150,000 miles or 5 years.

FEATURES & BENEFITS

- Matches each European vehicle manufacturer's technology and color requirements
- · Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and BS 6580
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the iob right

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT concentrate to perform a complete flush/fill or top-off.

Use PEAK ORIGINAL EQUIPMENT TECHNOLOGY 50/50 PREDILUTED ANTIFREEZE + COOLANT when just topping off your system.



A PERFECT MATCH FOR EVERY VEHICLE



FREEZE/BOIL PROTECTION CHART

Coolant/Water	PROTECTION FROM			
Ratio	Freezing Down to	Boiling Up to*		
50/50	-34°F (-36°C)	265°F (129°C)		
60/40	-62°F (-52°C)	270°F (132°C)		
70/30	-84°F (-64°C)	276°F (135°C)		

*Using a 15 psig (103 kPa) pressure cap in good condition



Available in both 50/50 Prediluted and Concentrate



ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT

APPLICATIONS

PEAK ORIGINAL EQUIPMENT TECHNOLOGY ANTIFREEZE + COOLANT for **EUROPEAN VEHICLES - VIOLET** is specifically engineered for use in all European vehicles requiring a VIOLET SILICATE-ENHANCED HYBRID ORGANIC ACID TECHNOLOGY extended life antifreeze + coolant:

Audi: 2007 and up

· Mercedes-Benz: 2014 and up

Porsche: 2010 and upVW: 2008 and up

PROPERTIES	TYPICAL VALUES ———					
PROPERTIES	ASTM TEST METHOD	CONCENTRATE	PREDILUTED (50/50)	ASTM D3306 Limits		
Appearance	Visual	Violet	Violet	Distinctive		
pH, (50% vol)	D1287	8.3	8.3	7.5-11.0		
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ / 1.065 min ²		
Boiling point³, °C (°F)	D1120	162.8 (325)	108 (226)	108 (226) Min		
Freezing point, °C (°F)	D1177		-38.8 (-37.8)	-36.4 (-33.5) Max		
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect		
Total water, mass %	D1123	<5	50	5 Max¹		
Ash content, mass %	D1119	<5	<2.5	5 Max ¹ / 2.5 Max ²		
Chloride, ppm	D3634	<25	<25	25 Max		

¹For concentrate product only, ²Prediluted (50/50) only, ³Unpressurized

SHIPPING INFORMATION



CONCENTRATE

PEVØB3

-**1 Gallon Bottle** 0-74804-06380-6 **6/1 Gallon Case** 0-74804-16380-3

PEVØB1 55 Gallon Drum0-74804-07042-2



50/50 PREDILUTED

– PEVB53

L1 Gallon Bottle 0-74804-06381-3

6/1 Gallon Case - 0-74804-16381-0

PEVB51 55 Gallon Drum0-74804-07032-3

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PEVØB3	Case	6/1 gal	16" L x 12.5" W x 12.25" H	60	36	20	2,210
PEVB53	Case	6/1 gal	16" L x 12.5" W x 12.25" H	57	36	20	2,102
PEVØB1	Drum	55 gal	23" dia x 35" H	544	4	20	2,226
PEVB51	Drum	55 gal	23" dia x 35" H	528	4	20	2,162

**Includes pallet weight of 50 lbs each

ADDITIONAL INFORMATION

Testing Requirements: For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

Storage Recommendations: PEAK Original Equipment Technology European VIOLET Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

Safety and Environmental Guidance: PEAK Original Equipment Technology European VIOLET Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from **peakauto.com**. Always dispose of used coolant in accordance with local, state and Federal guidelines.



Old World Industries, LLC. Northbrook, IL 60062 • 800-323-5440 **Peakauto.com**